


S1012-M



Ordering dimensions in blue

Surface roughness	$R_{t\max}$	R_a
Sliding surface	$\leq 2,5 \mu\text{m}$	$0,1-0,5 \mu\text{m}$
Bottom of groove	$\leq 6,3 \mu\text{m}$	$\leq 1,6 \mu\text{m}$
Groove face	$\leq 15 \mu\text{m}$	$\leq 3 \mu\text{m}$

Bearing area: 50–95% and a cutting depth of $0,5 R_z$ based on $C_{ref} = 0\%$

Standard dimensions		D	L	$R_{t\max}$	C	s^*
d	f8 over incl.	H10	+0,2			
mm						
5	40	d + 10	16	0,4	4	0,25
40	75	d + 15	25	0,4	5	0,38
75	150	d + 20	32	0,4	6	0,50
150	200	d + 25	40	0,4	8,5	0,63
200	300	d + 30	50	0,4	10	0,75
300		d + 40	63	0,4	13	1,00

* Extrusion gap values shown above are valid for a temperature of 70 °C, higher temperatures require lower values.

application



not bolded symbols; please consult our technical for application limitations

operating parameters & material

diameter range: up to 600 mm

material			temperature	max. surface speed	max. pressure ¹	hydrolysis	dry running	wear resistance
header ring S10-A	sealing element S11-M	back-up ring S12-M						
Ecotal/Ecomid ²	ECOPUR	Ecotal/Ecomid ²	-30 °C ... +100 °C	0,5 m/s	500 bar (50 MPa)	-	+	+
Ecotal/Ecomid ²	H-ECOPUR	Ecotal/Ecomid ²	-20 °C ... +100 °C	0,5 m/s	500 bar (50 MPa)	+	+	+
Ecotal/Ecomid ²	T-ECOPUR	Ecotal/Ecomid ²	-40 °C ... +100 °C	0,5 m/s	500 bar (50 MPa)	-	+	+
Ecotal/Ecomid ²	S-ECOPUR	Ecotal/Ecomid ²	-20 °C ... +100 °C	0,7 m/s	500 bar (50 MPa)	+	+	+
Ecotal/Ecomid ²	G-ECOPUR	Ecotal/Ecomid ²	-30 °C ... +100 °C	0,5 m/s	500 bar (50 MPa)	+	+	+
Ecoflon 2	Ecorubber 1	Ecoflon 2	-30 °C ... +100 °C	0,5 m/s	500 bar (50 MPa)	-	-	O
Ecoflon 2	Ecorubber 2	Ecoflon 2	-20 °C ... +200 °C	0,5 m/s	500 bar (50 MPa)	-	-	O
Ecoflon 2	Ecorubber 3	Ecoflon 2	-50 °C ... +150 °C	0,5 m/s	500 bar (50 MPa)	++	-	O
Ecoflon 2	Ecorubber H	Ecoflon 2	-25 °C ... +150 °C	0,5 m/s	500 bar (50 MPa)	+	O	+

the stated operation conditions represent general indications. it is recommended not to use all maximum values simultaneously.
surface speed limits apply only to the presence of adequate lubrication film.

¹ pressure ratings are dependent on the size of the extrusion gap.

² Ecotal up to ø260 mm, Ecomid above ø260 mm.

++ ... particularly suitable

o ... conditional suitable

+ ... suitable

- ... not suitable

for detailed information regarding chemical resistance please refer to our „list of resistance“. for increased chemical and thermal resistance rubber materials are to be preferred, polyurethane materials increase wear resistance. for higher gliding speeds another sealing system should be used (e.g. PTFE materials).


mode of installation

insert the male ring first, then the packing and finally the pressure ring (well greased) into the installation space. insert the metal insert without load, complete mounting of the system, tighten metal inserts slightly, let run in (10 to 20 idle strokes); re-tighten depending on leakage. in the case of wear, re-tightening is also possible.

if split rings are used, the packing should be fitted by separating the split ends axially (twisting). joints to be staggered 90 to 120 degrees relative to each other. the split ends are to be inserted first then the remaining seal ring is pressed in.

Ød	type of installation
≤ 6·cs	open mounting space required
> 6·cs≤ 10·cs	snap mounting with tool
> 10·cs	snap mounting by hand

recommended mounting space:



the adjustment range of the mounting space height (L) should correspond to approx. 10% of the theoretical mounting length. a guideline for the height of the spacer should be approx. 30% of the cross section.

recommended guide tolerance D1:

d f8 [mm]	p ≤ 100 [bar]	100 < p ≤ 200 [bar]	p > 200 [bar]
≤ 100	H10	H8	H8
> 100 ≤ 200	H10	H8	H7
>200	H9	H8	H7